

Technical Datasheet

tasker® TSK107 CPR- 2x10 AWG

Twisted Loudspeaker Cable for Fix Installation



CATEGORY Twisted Speaker Cable (See Audio Catalogue)
APPLICATIONS Loudspeaker cables for Fixed installation in constructions that require CPR certifications

- A:** Tubular Black **Flame retardant PVC AVML** Sheath.
Outer cable Diameter Ø 12,40 (±0,20) mm.
- B:** Core Insulation with **PE** Sheath, colored one Orange and one White.
Twist pitch 145 mm. Core Diameter Ø 5,00 (±0,20) mm.
- C:** O.F.C. red copper formation 84x0,30 mm.
Nom. Cross section 2x10 AWG.

MARKING tasker® TSK107 CPR 2x10 AWG O.F.C. – IMQ0051-CPR-1141 - 2017 – Eca –
Twisted Speaker Cable For Fix Installation – FirestoP® - Made In Italy

Cable Properties

Conductor Resistance	2,75 Ω/Km
Capacity Core/Core	60 pF/m.
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 11.04.25
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			