

MILAN S.r.l. a socio unico

Head Office – Export department:  
Viale Europa, 74  
20090 Cusago (MI) Italy  
T. +39 02 9039.4556-4158  
F. +39 02 9039.4551  
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione  
Viale Europa 72 Strada F12  
20090 Cusago (MI) Italy  
T. +39 02 9039.0037-0059  
F. +39 02 9039.0049  
www.tasker.it



## Technical Datasheet

# tasker® TSK406 CPR Cca – 2x6,00 mm<sup>2</sup>

## Fix Installation Speaker Cable



A	B	C
---	---	---

**CATEGORY** Fix Installation Speaker Cable (See News brochure)  
**APPLICATIONS** Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 12,00 (±0,20) mm.
- B:** Core Insulation in L.S.Z.H., colored one Red and one Black. Diam. Ø: 4,80 (±0,20) mm.
- C:** O.F.C. red copper formation 84x0,30 mm. Nom. Cross section 2x6,00 mm<sup>2</sup>.

**MARKING** tasker® TSK406 CPR Cca - 2x6,00 mm<sup>2</sup> - Loudspeaker Cable -0987-CPR-721 -Cca – s1–d1–a3 – FirestoP® - Halogen Free – Made in Italy

**NOTE** The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

### Cable Properties

<b>Conductor Resistance</b>	3,30 Ω/Km
<b>Max Rated Voltage</b>	100 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>		Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 22.01.24
	<b>X</b>	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			