

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® TSK1083 3x0,08 mm² (75Ω)

Special Video Flat Cable



CATEGORY Flat divisible video cable (See Video Catalogue)
APPLICATIONS R.G.B.Video and Audio Stereo assembly

- A:** Black **Flame Retardant PVC** Sheath.
Outer Dimension: 4,20x10,20 (±0,20) mm.
- B:** Soft PVC Sheath on single conductors colored Red, Green and Blue.
Diam. Ø 2,80 (±0,20) mm.
- C:** Braid shielding in S.P.C. silver plated copper, covering 90%.
- D:** Insulation with White PE. Diam. Ø 1,50 (±0,20) mm.
- E:** Stranded O.F.C. red copper formation 9x0,10 mm.
Nom. Cross section 3x0,08 mm² (75Ω)

MARKING **tasker®** TSK1083 3x75 OHM O.F.C. – R.G.B. CABLE FirestoP® Italy
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Video 75 Ω properties

Conductor Resistance	203 Ω/Km
Impedence	75 Ω
Velocity of Propagation	66 %
Capacity Core/Shield	67 pF/m
Max rated Voltage	49 V
Operative Temperature	-20/+70°C

Attenuation dB/100 m.

50 MHz	19,20
100 MHz	27,90
200 MHz	40,70
400 MHz	59,20
800 MHz	85,30
1000 MHz	101,00

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			