

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® TSK1054 – 4x0,12 mm²

Divisible Shielded Flat Cable



CATEGORY Shielded Flat Audio Cable (See Audio Catalogue)
APPLICATIONS Sound Reproduction and Electronics.

- A:** Night Blue Soft **PVC** Divisible Sheath.
 Outer cable Dimension 2,50x10,40 (±0,20) mm.
- B:** Each conductor has his own shielding in O.F.C. red copper
 spiral, covering 100%.
- C:** Core Insulation with PVC, colored Yellow, Blue, White, Red.
 Diam. Ø 1,10 (±0,10) mm.
- D:** Stranded formation in O.F.C. red copper 16x0,10 mm.
 Nom. Cross section 4x0,12 mm².

MARKING **tasker®** TSK 1054 4x0,12 mm² O.F.C. Individually Shielded Flat Cable
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.
PRODUCTION

Cable Properties

Conductor Resistance	140 Ω/Km
Capacity Core/Core	56 pF/m
Capacity Core/Shield	340 pF/m
Max Rated Voltage	49V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 26.09.24
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			