

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RNF3400 – 3x4,00 mm²

Heavy Duty Power Cable 450/750 V **Firestop®**



CATEGORY Heavy Duty Power Cable (See Electronics Catalogue)
APPLICATIONS Energy and electrical installation.

- A:** Black **Rubber** sheath, quality **EM2**. Chemical, Grease and Oils Resistant. Water Proof and good resistance to impact and heavy duty. Outer cable Diam. Ø 13,40 (±0,20) mm.
- B:** Core Insulation in **Neoprene rubber** quality **EI4**. Chemical, Grease and Oils Resistant. Water Proof and good resistance to impact and heavy duty. Diam. Ø 3,80 (±0,20) mm.
- C:** **O.F.C. red copper** formation with 0,25 mm elementary wires. Nom. Cross section 3x4,00 mm².

MARKING **tasker®** RNF3400 3G4.00 Extraflex Energy Cable 450/750 ICC IEMMEQU <HAR> H07RN-F 3G4,0

Cable Properties

| | |
|--|----------------|
| Conductor Resistance | 4,95 Ω/Km |
| Max Rated Voltage U₀/U | 450/750V |
| Max Short Circuit Temp. | 200°C/ 5 sec. |
| Mobile Bending Radius | 4x Outer Diam. |
| Fix Bending Radius | 3x Outer Diam. |
| Mobil Use Operative Temp. | -25/+60°C |
| Fix and protect Use Operative Temp. | -40/+60°C |

| | | | | | | | | | | |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|-----------------------|---------------------|----------|-------------------|
| USE | X | Indoor | Interno Edificio | INSTALLATION | X | Fixed | Fissa | INFORMATION | X | RoHS2 Compliant |
| Impiego | X | Outdoor Limited | Esterno Limitato | Posa | X | Flexible Limited | Flessibilità limitata | Informazioni | X | Ver. A / 15.07.16 |
| | X | Outdoor Use | Esterno | | | Dynamic (Drag Chain) | Mobile in Catena | | | |
| | X | Outdoor Direct Burial | Esterno Interrato | | | Dynamic (Torsion) | Mobile in Torsione | | | |