

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com


Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C283 – 1x2x0,22 + 3x1,50 mm² Special DMX 110 Ohm Cable

Firestop®

RoHS₃



CATEGORY DMX Cable + Power (See Audio Catalogue)

APPLICATIONS Active Digital Audio Cables

- A:** Black **Flame Retardant PVC**. Outer cable Diam. Ø 14,00 (±0,20) mm.
- B:** The single sheath are stranded with waste filler between conductors and wrapped with not woven polyester tape.

Digital Audio 110 Ohm Pair:

- C:** Black **Flame Retardant PVC**. Diam. Ø 4,00 (±0,20) mm.
- D:** Shielding O.F.C. red copper Spiral covering 100% + O.F.C. tinned copper Drain Wire.
- E:** Core Insulation with PEE, colored one Red and one Blue. Diam. Ø 1,50 (±0,20) mm.
- F:** O.F.C. tinned copper - formation 28x0,10 mm. Nom. Cross section 1x2x0,22 mm².

Three Power Conductors:

- G:** Black **Flame Retardant PVC**. Diam. Ø 7,20 (±0,20) mm.
- H:** Core Insulation with **Flame Retardant PVC** colored: Brown, Blue and Yellow/Green. Diam. Ø 3,00 (±0,20) mm.
- I:** O.F.C. red copper formation 48x0,20 mm. Nom. Cross section 3x1,50 mm².



MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

MARKING
CUSTOM
PRODUCTION

tasker® C 283 1x2x0,22 + 3x1,5 Digital DMX Cable - ITALY
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** with or without Metallic Armor.

Cable Properties

Digital Audio Cables Resistance	79,15 Ω/Km
Digital Audio Impedance	110 Ω
Power Conductor Resistance	12,50 Ω/Km
Capacity Core/Core	50 pF/mt
Capacity Core/Shield	89 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			