

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74  
20090 Cusago (MI) Italy  
T. +39 02 9039.4556-4158  
F. +39 02 9039.4551  
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12  
20090 Cusago (MI) Italy  
T. +39 02 9039.0037-0059  
F. +39 02 9039.0049  
www.tasker.it



## Technical Datasheet

# tasker® C702 Unshielded Twisted Pairs Cable



**CATEGORY** Unshielded Cable (See Data Network Catalogue)  
**APPLICATIONS** Data transmission and electronics.

- A:** Grey Soft **PVC** Sheath.  
Outer cable Diameter 4,50 (±0,20) mm.
- B:** The pairs are wrapped with transparent polyester tape.
- C:** The cores are insulated with PE – Diameter 0,90 (±0,20) mm.  
The color code is:  
1) White/Blue - Blue  
2) White/Orange - Orange
- D:** Stiff Wire conductor in O.F.C. Red Copper.  
Nominal cross section 2x2x0,22 mm<sup>2</sup>, formation 1x0,51 mm.

**MARKING** tasker® C702 – 2x2x0,22 mm<sup>2</sup> - O.F.C. – Unshielded Twisted Pair Cable –  
Made In Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,  
or Metallic Armored.

### Cable Properties

<b>Conductor Resistance</b>	90 Ω/Km
<b>Impedance</b>	100 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated