

## Technical Datasheet

# tasker® TSK1038 CPR Cca – 2x0,35 mm<sup>2</sup> DMX Digital Audio 110 Ohm Cable AES/EBU



A	B	C	D
---	---	---	---

**CATEGORY** Digital Audio Cable (See News brochure)  
**APPLICATIONS** Digital Audio application and DMX light on Fix Installation

- A:** Black L.S.Z.H. Sheath UV resistant.  
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 85%  
+ Aluminum foil tape.
- C:** The cores are stranded in a pair with two Flame Retardant PVC filler.  
Cores insulation in Foam PE, colored one red and one blue.
- D:** Diam. Ø 2,00 (±0,20) mm.
- E:** O.F.C. tinned copper stranded formation 7x0,25 mm.  
Nom. Cross section 2x0,35 mm<sup>2</sup>.

**MARKING** **tasker®** TSK1038 CPR Cca - 2x0,35 mm<sup>2</sup> – 110Ω DMX Audio Cable  
- 0987-CPR-722 – Cca – s1– d2–a3 – FirestoP® - Halogen Free  
- Made in Italy

### Cable Properties

<b>Conductor Resistance</b>	56,50 Ω/Km
<b>Capacity Core/Core</b>	46 pF/m
<b>Capacity Core/Shield</b>	92 pF/m
<b>Impedance</b>	110 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>		Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 05.09.22
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			