


Technical Datasheet

tasker® TSK912 CPR Cca – 12x2x0,25mm² **Fix Installation Digital Audio Multipair Cable**



CATEGORY Digital Multipair Audio Cable (See News brochure)
APPLICATIONS Audio Mixers and Benches

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 20,00 (±0,20) mm.
- B:** Total shielding with aluminum foil and tinned copper braid covering 80%.
- C:** The single pairs are isolated with black **L.S.Z.H.**, numbered from one to the number of elements and wrapped with proper fillers. Diam. Ø 3,80 (±0,20) mm.
- D:** The single pair are shielded with aluminum tape covering 100% + tinned copper drain wire.
- E:** The single cores are insulated with **foam PE**, colored one blue and one red. Diam. Ø 1,50 (±0,20) mm.
- F:** O.F.C. tinned copper formation 1x0,60 mm. Nom. Cross section 12x2x0,25 mm².

MARKING **tasker® TSK912 CPR Cca - 12x2x0,25 mm²** - Digital Audio Multipair cable
 AES/EBU 110Ω – CPR – Cca – s1–d1-a1 – FirestoP® - Halogen Free – Made in Italy

MILAN S.r.l. a socio unico

Head Office – Export department: **Ufficio Commerciale e Centro Distribuzione**
 Viale Europa, 74 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158 T. +39 02 9039.0037-0059
 F. +39 02 9039.4551 F. +39 02 9039.0049
 www.taskercables.com www.tasker.it

Cable Properties

Conductor Resistance	70 Ω/Km	Impedance	110 Ω
Capacity Core/Core	45 pF/m	Max Rated Voltage	49 V
Capacity Core/Shield	100 pF/m	Test Voltage	1500 V
Operative Temperature	-20/+80°C	Min. Bending Radius (Fixed)	7 x O.D.

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 11.12.24
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interato			Mobile in Dug Cham	Mobile in Canera			