

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C504 – 4x0,12 mm² - Spiral Shielded Cable



| | | | |
|---|---|---|---|
| A | B | C | D |
|---|---|---|---|

CATEGORY Shielded Multipolar Cable (See Data Network Catalogue)
APPLICATIONS Data transmissions, electronics and alarm systems.

- A:** Grey Soft **PVC** Sheath. RAL 7032
Outer cable diameter Ø 3,80 (±0,10) mm.
- B:** Spiral Shielding O.F.C. Red Copper covering 100%.
- C:** Cores Insulation with Soft PVC. DIN 47100 Standards..
Cores Diameter Ø 0,90 (±0,10) mm.
- D:** Stranded O.F.C. Red Copper formation 7x0,15 mm.
Nom. Cross section 4x0,12 mm².

MARKING tasker® C504 4x0,12 LOW VOLTAGE COMPUTER CABLE MADE IN ITALY
CUSTOM This product may be custom produced also in **LSZH, PE, PUR,**
PRODUCTION with or without Metallic Armor.

Cable Properties

| | |
|------------------------------|-----------|
| Conductor Resistance | 140 Ω/Km |
| Capacity Core/Core | 100 pF/m |
| Capacity Core/Shield | 200 pF/m |
| Max Rated Voltage | 49 V |
| Operative Temperature | -15/+70°C |

| | | | | | | | | | | |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|------------------|---------------------|----------|---|
| USE | X | Indoor | Interno Edificio | INSTALLATION | X | Fixed | Fissa | INFORMATION | X | RoHS2 Compliant |
| Impiego | | Outdoor Limited | Esterno Limitato | Posa | X | Restricted Mobile | Mobile Limitata | Informazioni | X | Ver. A / 15.02.18 |
| | | Outdoor | Esterno | | | Mobile | Mobile | | | |
| | | Outdoor Direct Burial | Esterno Interrato | | | Mobile in Drag Chain | Mobile in Catena | | | 10% measurement tolerance, unless otherwise indicated |