

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RG 59 AR 75 Ω Mil.- C17/F Standard Coaxial Cable – Outdoor Use



A	B	C	D	E
---	---	---	---	---

CATEGORY APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
 Premade video Cables and Broadcast.

- A:** Anti rodents **galvanized Iron Armor** specific for underground Installation even in presence of rodents.
Outer cable Diam. Ø 7,10 (±0,20) mm.
- B:** Black Soft **PVC** black sheath.
Outer cable diam. Ø 6,10 (±0,20) mm.
- C:** Shielding O.F.C. red copper Braid covering 98%.
- D:** Core Insulation with transparent PE. Dia. Ø 3,70 (±0,20) mm
- E:** Stiff Wire in CW, formation 1x0,58 mm.
Nom. Cross section 1x0,26 mm²

MARKING AVAILABLE ALSO

tasker® RG59 AR 75 Ohm Mil.- C17/F Armored Coaxial Video Cable - Made in Italy
 RG59 BU, RG59 Flex, RG59 Extra, RG59 LSZH, RG59 Special, RG59 PUR.

CUSTOM PRODUCTION

This product may be custom produced also in **PE**, and in all other versions with Metallic Armor.

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/mt
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-15/+70°C

Attenuation dB/100 m.

50 MHz	7,6
100 MHz	11,1
200 MHz	16,2
400 MHz	23,2
800 MHz	34,3
1000 MHz	38,7

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
	X	Outdoor	Esterno			Mobile	Mobile			
	X	Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			