

MILAN S.r.l. a socio unico

Head Office – Export department:
Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Halogen Free Technical Datasheet **Firestop®**

tasker® C908 LSZH – Digital SAT 75Ω Cable



A	B	C	D	E
---	---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS SAT installations and video premade cables.

- A:** White **L.S.Z.H.** sheath. Outer cable Ø 6,80 (±0,20) mm.
- B:** First Shielding O.F.C. tinned copper Braid covering 64%.
- C:** Second Shielding in Aluminum foil tape, covering 100 %.
- D:** Core Insulation with Gas Injected Foam PE. Diam. Ø 4,80 mm (±0,20) mm.
- E:** Stiff Wire in Red Copper - formation 1x1,13 mm.
Nom. Cross section 1x1,00 mm².

MARKING **tasker®** C908 LSZH coax 75-ohm gas injected – Digital SAT – Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in **PVC** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	18,80 Ω/Km
Capacity Core/Shield	52 pF/m
Velocity of Propagation	85%
Impedance	75 Ω
Max Tensile Strength	150 N
Voltage Insulation Sheath	4,5 Kv
Operative Temperature	-30/+70°C

Attenuation Test (dB/100 m.)

50 MHz	4,30
200 MHz	8,10
470 MHz	12,60
1000 MHz	18,50
1750 MHz	25,10
2400 MHz	30,20
3000 MHz	33,50

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			