

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

✓  
**RoHS<sub>2</sub>**  
 2002/95/EC  
 2011/65/UE



**Firestop® Technical Datasheet**

**tasker® C8100 CPR – 8x1,00 mm<sup>2</sup>  
 Braided Shielded Cable**



A	B	C	D
---	---	---	---

**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture does not represent the real number of conductors  
 Braided Conductor Shielded Cable (See Data Network Catalogue)  
 Data transmission and Electronics

- A:** Black **Flame Retardant PVC** sheath.  
Outer cable diam. Ø 11,20 (±0,20) mm.
- B:** Braided Shielding O.F.C. Red Copper covering 85%.
- C:** Cores Insulation with **Flame Retardant PVC**.  
Core color code: Brown, Blue, Black, Yellow/Green, Red, White, Yellow, Grey. Diam. Ø 2,60 (±0,20) mm.
- D:** Stranded O.F.C. Red Copper formation 32x0,20 mm.  
Nom. Cross section 8x1,00 mm<sup>2</sup>.

**MARKING**

**tasker® C8100 CPR 8x1,00 mm<sup>2</sup> O.F.C. - IMQ 0051-CPR-0966 – 2017 – Eca –  
 BRAIDED SHIELDED CABLE - Firestop® - Made Italy**

**Cable Properties**

<b>Conductor Resistance</b>	18,80 Ω/Km
<b>Capacity Core/Core</b>	120 pF/mt
<b>Capacity Core/Shield</b>	220 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			